Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	4	(("5230459") or ("5653856") or ("5836506") or ("6164519")).PN.	USPAT	OR	OFF	2005/08/03 09:08
L2	573	(sputter\$4 same target) and (back or backing or backup or back adj up or "back-up") same plate and solder\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/08/03 09:10
L3	278	2 and (groov\$4 or notch\$4 or rough or rough\$6 or roughen\$4 or ridge\$4 or interlock\$4 or salient\$4 or mating\$4)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/08/03 09:10
L4	7531	((228/128,135,136,141.1,245,246, 165-167,170-173.1,174) or (204/298.12,298.13,192.12)).CCLS.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/08/03 09:09
L5 .	193	4 and (sputter\$4 same target) and (back or backing or backup or back adj up or "back-up") same plate and solder\$4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2005/08/03 09:10
L6	120	5 and (groov\$4 or notch\$4 or rough or rough\$6 or roughen\$4 or ridge\$4 or interlock\$4 or salient\$4 or mating\$4)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/08/03 09:10
L7	20	6 and (groov\$4 or notch\$4 or rough or rough\$6 or roughen\$4 or ridge\$4 or interlock\$4 or salient\$4 or mating\$4) near (height or depth or deep or high or inch\$4 or micron or micrometer or ".mu.m" or "mu.m")	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/08/03 09:11